

EVINRUDE

E-TEC

PERFORMANCE REPORT

BULLETIN #: 1142

ENGINE 1: E300XU

Engine 2: E300XCU

BOAT TYPE: Offshore

DATE OF TEST: 3/4/2015

BRP US, Inc.
10101 Science Drive
Sturtevant, WI 52177
www.evinrude.com



Dusky Marine, Inc.
110 North Bryan Road
Dania, FL 33004
954-922-8890
www.dusky.com

2015 Dusky 33 Open Fisherman

BOAT

2015 Dusky 33 Open Fisherman

Material	Fiberglass
Length	33'
Beam	10' 10"
Weight w/o Engine	6700 LBS
Maximum HP	900 HP
Fuel Capacity	260 Gallons
Transom Height	25"
Steering	I Dock

ENGINE

Twin Evinrude® E-TEC™ G2™ 300 HP

Engine Type	74° V-6
Horsepower	300
Displacement	3.4 Liter
Induction	ETEC DI
Operating Range	5400 - 6000 RPM
Weight	569 LBS Dry Weight
Gear Ratio	1.85:1

PROPELLER

Evinrude® Rebel™

Material	Stainless
Diameter/Pitch	15 1/8" X 20"
No. of Blades	3
Part Number	763992

MOUNTING HEIGHT

Hole Position	#2
Jack Plate	No
AV Mounting	N/A

PERFORMANCE DATA

RPM	MPH	GPH	MPG	RANGE
500	2.70	0.60	4.50	1053
1000	5.70	1.35	4.22	988
1500	8.10	2.90	2.79	654
2000	9.35	6.15	1.52	356
2500	11.10	9.55	1.16	272
3000	17.85	12.10	1.48	345
3500	24.60	15.15	1.62	380
4000	33.60	20.10	1.67	391
4500	39.05	24.05	1.62	380
5000	45.90	30.15	1.52	356
5500	51.80	35.20	1.47	344
5975	56.15	47.60	1.18	276

Fuel Data Range (Miles) Based On 90% Fuel Capacity

TEST CONDITIONS

Water Conditions	Light Chop
Wind Velocity	16 to 20 MPH
Air Temperature	82° F
Fuel Load	200 Gallons
Weight	1 Person (250 Lbs), Fuel, test & safety gear, 4 Batteries, Soft T-top, iDock

PERFORMANCE SUMMARY

Top Speed	56.2 MPH
Best Fuel Efficiency	1.67 MPG For 391 Miles @ 33.60 MPH
Acceleration	4.2 seconds to plane

NOTE: Data may vary due to changes in weather and water conditions, elevation, load and boat bottom conditions, boat, engine and propeller options and conditions, and operator ability. Speed and fuel were calculated by NMEA 2000 I-Command. Test performed and certified by BRP OEM Applications Engineering.

© 2015 BRP US Inc. All rights reserved.™ ® and the BRP logo are Trademarks and Registered Trademarks of Bombardier Recreational Products Inc. or its affiliates.

EVINRUDE
E-TEC®

